



* Hidden by Pipe cover

Standard Connection Sizes

- (A) Cold DN20 3/4" BSP
 (B) Gas DN20 3/4" BSP
 (C) Hot DN20 3/4" BSP
 (D) Electrical Normal - 95W
 Standby - 2W (with 1 water control)
 Standby with Anti-frost protection - 120W
 Max output - 48.8kW

Specifications

Max Water Pressure 1000kPa
 Min Water Pressure 200 kPa
 Water Pressure Relief Valve open- 2060kPa close- 1470 kPa
 LPG and NG Max Gas Consumption 210 MJ/h
 Gas Pressure LPG 2.75-3.0 kPa
 Gas Pressure NG 1.13-3.0 kPa
 Gas Pressure Max 3.5kPa
 Noise level 54dB(A)
 Weight 21kg

For further information check - rinnai.co.nz

Rinnai NZ Limited
 105 Pavilion Drive
 Mangere, Auckland
 2022

Rinnai Infinity with R1417 Pipe cover
 INFHD49FFL HD49 Internal Commercial LPG
 INFHD49FFN HD49 Internal Commercial NG
 INFA28FFL A28 Internal Infinity LPG
 INFA28FFN A28 Internal Infinity NG

Designed:	Spec #:
Drawn: KS	Date: 5/05/22
Scale @ A4: 10:1	Rev: